





WP6 Planning From D6.2 to D6.3

January 9, 2009

Giorgio Zoia, eyeP Media SA




- Design of the BMBA-enabled soft-phone
 - overall system architecture and prototype interfaces
- A few words about EPM softphones
- A few words about EPM media stack
- Baseline systems integration
- Example and templates
- D6.3 and work-plan for D6.3





EPM “Mercury” softphone system architecture

- A multi-process architecture
- IPC daemon based on dbus
 - dbus is a “low-bitrate” communication system
- UI and related controllers are attached as dbus modules
- The real-time telephony module (SIP component + media stack) is a single monolithic module with all the signal rate processing and control
- Configuration and user data stored in the MIB (Management Information Base)
 - MIB data can be encrypted




Main Architectural Elements





EPM media stack architecture

- A typical data-path media flow stack
- Transmission, coding and processing functionality encapsulated in *filters*
- *filters* are organized into *pipes* (one or more filters in cascade)
- Separated pipes for audio and video flows
- Working at a typical 10-30 ms clock
 - more later on about this



End user perspective



■ Protocol support


- RTP/RTCP : RFC 1889, RFC 1890 (AVT Profiles), RFC 2833 (DTMF over RTP), draft-ietf-avt-profile-new-12.txt (updated AVT profiles)
- IMS (data protection on control, in 6 months on data)
- Firewall NAT traversal

■ Signal Processing –Voice & Video



- VAD, AGC, CNG, Noise Reduction, Echo Suppression
- SR Converter, Mixer
- Speech coders (Narrow Band, Wide Band)
- Video coders (automatic coder adaptation to CPU, System, etc.)

■ Extended Feature Set – Extended Services



- Conference (audio and video)
- Play Files over IP & Record
- Signal generator (tones, etc.)





Media stack concepts





Typical Data Path Diagram




- Plug-ins only for codecs and transport
- Take a look at EMStreamFilter.h (D6.2)
- Periodical execution over a “frame” of data
- Ability to react to control-rate changes at typical rates and settings
 - sampling rate for audio
 - frame rate and/or frame size for video
- Process in a *pipelined* way for video. Feasible ?



MOBIO sample Data Path Diagram




- It is crucial for development process to agree on platform for development. The platform must fulfill the following requirements
 - *Provide SDK for PCs*
 - *Support a true simulation of the device on PCs. This feature is especially crucial when working with multimedia components like cameras and microphones.*
 - *Offer a wide range of devices, from high-end PDAs to smart-phones and ordinary mobile phones.*




A few remarks (from EPM)

- Windows OS (desktop and mobile) so far
 - No real evidence of real business being developed based on Linux distributions, too much unclear even for mobile
 - No real evidence whether phone applications in the Apple mobile devices (cellular and/or IP) will be open or not
- Often using XML-based format to exchange data internally (e.g. to/from plug-ins)
 - Define a *data* buffer ?
- Warning: mobile devices do not have a swap disk!
Easily out of RAM, especially when using large open source libraries (...WP5, care about coding)




- System specification (stage 3) and prototype implementation with draft biometric modules
 - user device simulated using a laptop
- *A version of the API is released by EPM and prototype implementation started according to the system current specification*
- *Other partners start implementing the API. It is expected that during this step some improvements and enhancements in the API will be proposed*
- *Proposals to improve the current API will be taken into account and the API definition updated. The whole process then iterates from the first step*



Further issues about the soft phone

- Information about setup of filters
 - does something need to be configurable in a per-user way ?
- Control and User Interface layers
 - necessary to specify asap necessary UI look and behavioral specification (all)
 - necessary to specify asap exact use case(s) and consequently test case scenarios (EPM, all)



Action points for the next few months

- EPM: Prune UCs to 1-2 final candidates for actual implementation
- All Partners: Functional requirements on User layer
- EPM: provide code template for an example media stack filter (will be selected internally)
- All Partners: identify external libraries and what kind of code is used out of that
- EPM-UAPV: talk about real-time processing of frames

